


Dust-Explosion Protected Escape Sign Luminaire D22-Ex 6011.1 CG-S



- Dust explosion-protected escape sign luminaire with 8W fluorescent lamp
- Available for wall and ceiling mounting
- Shortened inspection effort due to **CEWA GUARD** technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditure with **STAR** technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit



D22-Ex 6011.1 CG-S






D22-Ex 6011.1 CG-S

Marking acc. to 94/9/EG	Ex II 3 D Ex tD A22 IP55 T80°C
EU-type inspection certificate	BVS 07 ATEX E 129X
Viewing distance	approx. 26 m
Housing material	Polycarbonate (850 °C glow wire resistant), light grey
Housing colour	Grey RAL 7035
Protective cover	Polycarbonate
Rated voltage	AC: 230 V ± 10 %, 50-60 Hz DC: 220 V + 25 % - 20 %
Rated power	approx. 16 VA
Current consumption with battery operation	approx. 30 mA
Protection rate EN 60529	IP 55
Insulation class	I
Permissible temperature range	-10 °C to +40 °C
Cable infeeds	1 x EEx e-cable entry M20 x 1.5 1 x EEx e-blanking plug M20 x 1.5
Connection terminals	3 x Loop terminals 2.5 mm ²
Dimensions in mm (L x H x T)	400 x 160 x 103
Type of mounting	Wall and ceiling mounting
Light source	8 W fluorescent lamp T5
Weight	approx. 1.4 kg

Ordering details

Dimensions in mm



Type	Scope of supply	Order No.
D22-Ex 6011.1 CG-S acc. to DIN 4844	Luminaire with CG-S module and 20-digit address switch, with cover incl. three pictograms PL, PR, PU	 4 0071 349 520
D22-Ex 6011.1 CG-S	Luminaire with CG-S module and 20-digit address switch, with cover incl. three pictograms PL, PR, PU	 4 0071 352 710