

# ATIK DC



**IP 65 luminaire in a modern design, appropriate for urban lighting applications.**

#### Materials

- Body and arm: die-cast aluminium
- Reflector: anodised aluminium
- Diffuser: transparent methacrylate resistant to hits (ARI trans)
- Latch system: four levers in die-cast aluminium

#### Lamps

- HPS ovoid (50W to 150W)
  - MH ovoid (50W to 150W)
  - Use HPS 70W lamps without built-in ignitor.
- Lampholder: E-27 and E-40  
Supplied without Lamps

#### Gear

Compatible with lamps HPS, MH and M. For HPS-MH versions use MH lamps according to the intensity table (A), page 23

#### Installation

- Pole of Ø 60mm, 70mm long

#### Certificates

According to EN-60598-1 & 2-3

#### Remarks

Supplied with 5m of cable, 2,5mm<sup>2</sup> section.

#### TECHNICAL SHEET

##### PROTECTION LEVEL

IP 65  
Class or   
IK09

##### REFLECTOR

- RC, RF- road lighting E2
- SC, SF, SV- lamellas anti-glare E3
- OC, OF, OV- opaque E5

##### SPEC. TECHNICAL

230V-50Hz

- 0,18/0,23 m<sup>2</sup>
- 15 kg
- 

##### COLOURS

GY9007 -grey RAL 9007-  
other colours: consult quantity and price

##### CERTIFICATES



#### VERSIONS ATIK DC

ATIK DC -RC-



ATIK DC -RF-



\* These versions are also available with flat diffusers. See ATIK DF, pag. 106)

ATIK DC -SC-



ATIK DC -SF-



ATIK DC -SV-



ATIK DC -OC-



ATIK DC -OF-



ATIK DC -OV-

