



Technical data

Ex-d control stations Type EFS

Marking to 94/9/EC	Ⓔ II 2 G Ex d IIC T6 / Ⓔ II 2 D IP67 T 85 °C
EC-Type Examination Certificate	LOM 03 ATEX 2034
IECEX Certificate of Conformity	IECEX BK1 07.0027
Marking accd. to IECEX	Ex d IIC T6 Ex tD A21 IP67 T80 °C
Permissible ambient temperature	-20 °C to +55 °C
Rated voltage	max. 660 V AC
Rated current	max. 20 A
PE connecting terminals	2 x 2.5 mm ² / PE ext.: 2 x 6 mm ²
Insulation class	I
Incandescent lamp	230 V 3 W
Degree of protection accd. EN 60529	IP67
Cable glands/Gland plates/Enclosure drilling	1 x 3/4" ISO 7/1 or 2 x 3/4" ISO 7/1, one plugged
Enclosure material	Light alloy
Enclosure colour	natural finish

Other versions available on request

Ordering details

Type	Version	Weight	Order No.
Control units			
EFS A	1 x pushbutton, 1 NO + 1 NC, label "White"	0.75 kg	NOR 000 114 110 511
EFS A/A	2 x pushbutton, 1 NO + 1 NC, label "I - 0"	0.85 kg	NOR 000 114 110 553
EFS D	1 x mushroom head pushbutton, 1 NO + 1 NC, label "0"	0.80 kg	NOR 000 114 110 587
EFS A/D	1 x pushbutton 1 NO, 1 x mushroom head pushbutton NC, label "I - 0"	0.85 kg	NOR 000 114 110 540
EFS L	1 x alarm pushbutton, 1 NO + 1 NC, with windows	0.85 kg	NOR 000 114 110 595
EFS A/A/A	3 x pushbutton, 1 NO + 1 NC, label "0 - I - II"	1.50 kg	NOR 000 114 110 747
EFS A/A/V	2 x pushbutton, 1 NO + 1 NC, label "0 - I - II", 1 x green signal lamp	1.50 kg	NOR 000 114 110 748
EFS 72	With measuring instruments 72 mm x 72 mm	1.20 kg	NOR 000 114 110 740

Type	Version	Weight	Order No.
Control switches			
EFS I	0 - 1	0.90 kg	NOR 000 003 110 945
EFS H	1 - 2	0.90 kg	NOR 000 003 110 937
EFS J	1 - 0 - 2	0.90 kg	NOR 000 003 110 953
EFS P	0 - 1	0.90 kg	NOR 000 003 110 995
EFS P40	0 - 1	0.90 kg	NOR 000 114 110 738