

Stair Safety Luminaire

91.1 CG-S

EN
1838


4 W



IP54

CG-S

- Stair safety luminaire of diecast aluminium for recessed mounting
- High degree of protection of IP54
- Optionally with opaque plastic cover or black grid cover
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditure with STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit



91.1 CG-S
with grid cover









91.1 CG-S
with pictogram PL

Luminous flux Φ_E/Φ_N at the end of rated operating time	75 %
Housing material	Aluminium diecast
Weight incl. cover	0.76 kg
Housing colour	White / Black
Type of mounting	for recessing into stairs
Connection terminals	Loop terminals 3 x 2.5 mm ²
Connection voltage	220 - 240 V, 50/60 Hz 176 V - 275 V DC
Current consumption with battery operation	20 mA
Power consumption mains operation	8 VA
Permissible ambient temperature	-10 °C to +40 °C
Light source	4 W/T16

Ordering details

Type	Scope of supply	Order No.
91.1 CG-S	Complete with CEWA GUARD monitoring and 20-digit address switch, with opaque cover	4 0071 341 920
91.1 CG-S	Complete with CEWA GUARD monitoring and 20-digit address switch, with grid cover	4 0071 340 621

Accessories

Type	Order No.
Concrete mounting box	4 0071 079 752
Recessed wall mounting box (cavity wall mounting set cut-out 230 mm x 90 mm)	4 0033 079 456
Cover PL acc. to DIN 4844	 4 0071 349 642
Cover PR acc. to DIN 4844	 4 0071 349 643
Cover PU acc. to DIN 4844	 4 0071 349 644
Cover PL	 4 0071 345 011
Cover PR	 4 0071 345 012
Cover PU	 4 0071 345 013

Dimensions in mm

