

# LED Portable Emergency Lights

## W 276.3/4 LED, W 276.3/7 LED

IP54





- LED handheld torch with emergency light function: monitoring of the charging circuit and function display via green LED
- Robust construction of impact-resistant, non-abrasive plastic
- Integrated charger – connection via flexible spiral cable with EURO plug
- Main beam consists of 3 High Power LEDs with narrow distribution reflector optic
- Main beam output can be set: Eco mode for longer battery operation (3.0 W) or boost mode for increased luminous flux (5.5 W)
- Ancillary light with 6 x 3 chip LEDs (1.5 W) and wide light distribution
- More than six times the light quantity compared to variant with incandescent lamp
- Includes three slip-on filters (red, orange, clear prismatic) for modification of light distribution and signalling
- Flashing light function
- Up to 14 h light (ancillary light) and 5.5 h (Eco main beam) with 4 Ah battery
- Up to 27.5 h light (ancillary light) and 9 h (Eco main beam) with 7 Ah battery
- Long range up to 50 m at 1.5 lx illuminance



W 276.3/4 LED

Filters (incl.)	Red, orange, clear prismatic	
Photometric data (Main beam)	Irradiance I max = 3720 cd / Half value angle = 12,4° Illuminance: 150 lx @ 5 m, 6 lx @ 25 m, 1,5 lx @ 50 m	
Housing material	impact resistant, non-adhesive plastic	
Housing colour	grey	
Emergency duration	4 Ah battery 5,5 h Eco (main beam) 3,5 h Boost (main beam) 14,0 h (ancillary light)	7 Ah Battery 9,0 h Eco (main beam) 6,0 h Boost (main beam) 27,5 h (ancillary light)
Battery	rechargeable, maintenance free and gas tight NC-Accu - 4,8 V / 4 Ah - 4,8 V / 7 Ah	
Light source	3 x HighPower-LED	
Main beam	3,0 W - 240 lm (Eco) / 4,5 W - 330 lm (Boost)	
Ancillary light	6 x MidPower-LED 1,5 W - 65 lm	lm = luminaire flux
Connection voltage	230 V 50/60 Hz	
Mains power supply load	10 VA	
Insulation class	II	
Degree of protection	IP54	
Switch function	Flashlight, maintained light and ancillary light	
Monitoring function	Charging indication by green LED	

Dimensions in mm



Wall bracket

### Ordering details

Type	Battery	Order No.
W 276.3/4 LED	4 Ah	4 0071 352 032
W 276.3/7 LED	7 Ah	4 0071 352 033

### Accessories / spare parts

Type	Order No.
Rechargeable NC-Accu 4.8 V/4 Ah	4 0071 345 248
Rechargeable NC-Accu 4.8 V/7 Ah	4 0071 345 253
Shock-power wall mounted holder	4 0071 344 274
Wall bracket	1 1145 000 492
Mains connection lead	4 0018 031 358
Slip-on filter set red, orange and clear prismatic	2 1145 995 000