

Safety Luminaire and Escape Sign Luminaire Style 51021 CG-S





- Compact escape sign or safety luminaire with three-sided light emission, of high quality, UV-resistant, halogen-free plastic
- Modular constructed luminaire series permits combination with various fixing modules
- Includes opaque cap with simple snap mounting and pictogram foil set
- Simple mounting via quick mounting set (can be pre-assembled) with integrated terminal block for through-wiring
- Optionally available IP54 set (for electronic and light source) for increased sealing requirements for indoor rooms or for canopied outdoor areas
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditure with STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit



51021 CG-S
with pictogram foil

Viewing distance	17 m
Luminous flux Φ_E/Φ_N at the end of rated operating time	75 %
Housing material	Polycarbonate (850 °C glow wire resistant)
Weight incl. cover	0.6 kg
Housing colour	Grey
Type of mounting	Ceiling mounting
Connection terminals	Loop terminals 3 x 2.5 mm ²
Connection voltage	220 - 240 V, 50/60 Hz 176 - 275 V DC
Current consumption - battery operation (220 V)	30 mA
Power consumption mains operation	16 VA
Permissible temperature range	-10 °C to +40 °C
Light source	8 W/T16, 450 lm

Ordering details

Type	Scope of supply	Order No.
51021 CG-S set acc. to DIN 4844	Luminaire housing with high cover, quick-mounting set and 3 pictogram foils PL/PR/PU, with CEWA GUARD monitoring and 20-digit address switch 	4 0071 348 171
51021 CG-S set	Luminaire housing with high cover, quick-mounting set and 3 pictogram foils PL/PR/PU, with CEWA GUARD monitoring and 20-digit address switch 	4 0071 352 707

Accessories

For accessories see page 1/51

Dimensions in mm

