

Portable Emergency Lights with Emergency Lighting Function W 270.3/4, W 270.3/7



- Robust handheld torch with emergency lighting function (non maintained mode)
- Housing of impact-resistant, non-abrasive plastic
- External charger for low luminaire weight
- Including three C-washers (red, orange, clear prismatic) for modification of light distribution and signalling
- Up to 12 h light (auxiliary light operation) and 3.5 h with full power with 4 Ah battery
- Up to 25 h light (auxiliary light operation) and 6.5 h with full power with 7 Ah battery
- Flashing light function
- High range up to 80 m at 1 lx illuminance



W 270.3/4



Charging unit Z 345.3
for portable emergency lights
W 270.3/4 and W 270.3/7

Housing material	impact resistant, non-adhesive plastic
Housing colour	Grey
Duration of emergency lighting Battery 4 Ah (7 Ah)	3.5 h (6.5 h) with incandescent lamp 5 V/5 W (main beam) 12.0 h (25.0 h) with incandescent lamp 4.8 V/1.5 W (pilot beam)
Battery	rechargeable, maintenance free and gas tight NC-Accu 4.8 V / 4 Ah NC-Accu 4.8 V / 7 Ah
Light source	Main beam 5 V / 5 W Pilot beam 4.8 V / 1.5 W
Connection voltage (charging unit)	230 V 50/60 Hz
Rated load (charging unit)	10 VA
Switch function	Flashlight, maintained light and pilot light

Ordering details

Type	Battery	Order No.
W 270.3/4	4 Ah	1 1145 000 270
W 270.3/7	7 Ah	1 1145 000 272

Accessories/spare parts

Type	Order No.
Charging unit Z 345.3	4 0071 341 145
Incandescent lamp 5 V / 5 W (5 pcs.)	4 0071 345 265
Incandescent lamp 4.8 V / 1.4 W (10 pcs.)	4 0071 345 264
Rechargeable NC-Accu 4.8 V/4 Ah	4 0071 345 248
Rechargeable NC-Accu 4.8 V/7 Ah	4 0071 345 253
Slip-on filter set red, orange and radial difuser cap	2 1145 995 000

Lighting engineering

Distance	Illumination
5 m	256 lux
20 m	16 lux
80 m	1 lux

*) valid for luminaire, charging unit IP 44